


20W POLYCRYSTALLINE SOLAR MODULE




ELECTRICAL CHARACTERISTICS

Power	20W		
Operating Voltage	18V	Open Circuit Voltage	21.6V
Operating Current	1.11A	Short Circuit Current	1.3A
Type of solar cell	Polycrystalline Silicon Solar Cell		
Power Tolerance	±5%		
STC: Irradiance 1000W/m ² , Module temperature: 25°C, AM=1.5			

MECHANICAL SPECIFICATIONS

Dimensions	530×350×25mm
Encapsulation	Glass/EVA/Cells/EVA/TPT
Front Glass	Tempered Glass, thickness: 3.2mm
Frame	Anodized aluminum alloy (Silver)
Output lead wire	Without solder wire, with junction box
Dimension Tolerance: ±0.2mm Efficiency: ≥15.8%	

FIGURE OF STRUCTURE



WARRANTIES

Power output more than 90% for 10years
 Power output more than 80% for 25years
 Working life 25years

TEMPERATURE COEFFICIENTS

Nominal Operating Cell Temperature (NOCT): 45°C±2°C	
Temp.Coefficient of Isc	(0.045±0.01)%/°C
Temp.Coefficient of Voc	-(0.34±0.01)/°C
Temp.Coefficient of Power	-(0.47±0.05)%/°C

TESTED OPERATING CONDITIONS

Max load	50psf 245kg/m ² (2400)pascals
Hailstone impact	25mm(1inch) at 23m/s(52mph)
Operating Temperature	-40° C to + 85° C

THE TECHNICAL FILES PROVIDED BY CHINA SOLAR LTD

Office Address:
 N0.401, ZhongKang Pioneer Park, ZhongKang Road,
 Futian District, ShenZhen City, Guangdong Province, China
 Factory Address:
 Longxi Hi-tech Industrial Park, Longcheng Road, Longgang
 Town, ShenZhen City, Guangdong Province, China